

Amendments of the Claims

The following listing of claims, if entered, will replace all prior versions, and listings, of claims in the above-identified patent application:

Listing of Claims

1. (previously presented) A phase-locked loop circuit for use in a programmable logic device, said phase-locked loop circuit having an input terminal for receiving an input signal having a reference frequency and an output  
5 terminal for outputting an output frequency phase-locked to said reference frequency, and comprising:  
an oscillator for producing said output frequency; and  
a feedback path feeding said oscillator, said  
10 feedback path accepting as inputs said reference frequency and said output frequency, and causing said oscillator to drive said output frequency to a phase-frequency lock with said reference frequency, said feedback path comprising at least one component connected therein; wherein:  
15 one or more of said at least one component is programmably connectable to another portion of said programmable logic device for operation of said another portion of said programmable logic device with said one or more of said at least one component.
2. (previously presented) The phase-locked loop circuit of claim 1 wherein, when said phase-locked loop circuit is not in use in said programmable logic device, said one or more of said at least one component is available for use by  
5 said another portion of said programmable logic device.
3. (previously presented) The phase-locked loop circuit of claim 1 wherein, when said phase-locked loop circuit is in use in said programmable logic device, said another

portion of said programmable logic device is available to be  
5 substituted in said phase-locked loop circuit for said one or  
more of said at least one component.

4. (previously presented) The phase-locked loop  
circuit of claim 1 wherein said at least one component  
comprises:

a phase-frequency detector having as inputs said  
5 reference frequency and said output frequency, said phase-  
frequency detector outputting a comparison signal indicating a  
relationship between said reference frequency and said output  
frequency;

an analog front end circuit having said  
10 comparison signal as an input and outputting an analog voltage  
signal indicative of said comparison;

an analog-to-digital converter having said  
analog voltage signal as an input and outputting a digitized  
voltage signal;

15 a digital signal processor having said digitized  
voltage signal as an input and outputting a digital control  
signal; and

a digital-to-analog converter having said  
digital control signal as an input and outputting an analog  
20 control signal that is input to said oscillator.

5. (original) The phase-locked loop circuit of claim  
4 wherein said analog-to-digital converter has at least one of:

a second input from a first said another portion  
of said programmable logic device; and

5 a second output to a second said another portion  
of said programmable logic device.

6. (original) The phase-locked loop circuit of claim  
5 wherein said first said another portion is a pin of said  
programmable logic device.

7. (original) The phase-locked loop circuit of claim 5 wherein said first said another portion is in core logic of said programmable logic device.

8. (original) The phase-locked loop circuit of claim 5 wherein said second said another portion is a pin of said programmable logic device.

9. (original) The phase-locked loop circuit of claim 5 wherein said second said another portion is in core logic of said programmable logic device.

10. (previously presented) The phase-locked loop circuit of claim 4 wherein said digital signal processor has at least one of:

a second input programmably connectable to a  
5 first said another portion of said programmable logic device;  
and

a second output programmably connectable to a  
second said another portion of said programmable logic device.

11. (original) The phase-locked loop circuit of claim 10 wherein said first said another portion is a pin of said programmable logic device.

12. (original) The phase-locked loop circuit of claim 10 wherein said first said another portion is in core logic of said programmable logic device.

13. (original) The phase-locked loop circuit of claim 10 wherein said second said another portion is a pin of said programmable logic device.

14. (original) The phase-locked loop circuit of claim 10 wherein said second said another portion is in core logic of said programmable logic device.

15. (previously presented) The phase-locked loop circuit of claim 4 wherein said digital-to-analog converter has at least one of:

a second input programmably connectable to a  
5 first said another portion of said programmable logic device;  
and

a second output programmably connectable to a second said another portion of said programmable logic device.

16. (original) The phase-locked loop circuit of claim 15 wherein said first said another portion is a pin of said programmable logic device.

17. (original) The phase-locked loop circuit of claim 15 wherein said first said another portion is in core logic of said programmable logic device.

18. (original) The phase-locked loop circuit of claim 15 wherein said second said another portion is a pin of said programmable logic device.

19. (original) The phase-locked loop circuit of claim 15 wherein said second said another portion is in core logic of said programmable logic device.

20. (original) The phase-locked loop circuit of claim 4 wherein said analog front end circuit comprises a charge pump.

21. (previously presented) The phase-locked loop circuit of claim 1 wherein said at least one component comprises:

a phase-frequency detector having as inputs said  
5 reference frequency and said output frequency, said phase-frequency detector outputting digital comparison signals

indicating a relationship between said reference frequency and said output frequency;

10 a digital counter circuit having said digital comparison signals as inputs and outputting digital count signals indicative of said comparison;

a digital signal processor having said digital count signals as inputs and outputting a digital control signal; and

15 a digital-to-analog converter having said digital control signal as an input and outputting an analog control signal that is input to said oscillator.

22. (previously presented) The phase-locked loop circuit of claim 21 wherein said digital signal processor has at least one of:

5 an additional input programmably connectable to a first said another portion of said programmable logic device; and

a second output programmably connectable to a second said another portion of said programmable logic device.

23. (original) The phase-locked loop circuit of claim 22 wherein said first said another portion is a pin of said programmable logic device.

24. (original) The phase-locked loop circuit of claim 22 wherein said first said another portion is in core logic of said programmable logic device.

25. (original) The phase-locked loop circuit of claim 22 wherein said second said another portion is a pin of said programmable logic device.

26. (original) The phase-locked loop circuit of claim 22 wherein said second said another portion is in core logic of said programmable logic device.

27. (previously presented) The phase-locked loop circuit of claim 21 wherein said digital-to-analog converter has at least one of:

a second input programmably connectable to a  
5 first said another portion of said programmable logic device;  
and

a second output programmably connectable to a second said another portion of said programmable logic device.

28. (original) The phase-locked loop circuit of claim 27 wherein said first said another portion is a pin of said programmable logic device.

29. (original) The phase-locked loop circuit of claim 27 wherein said first said another portion is in core logic of said programmable logic device.

30. (original) The phase-locked loop circuit of claim 27 wherein said second said another portion is a pin of said programmable logic device.

31. (original) The phase-locked loop circuit of claim 27 wherein said second said another portion is in core logic of said programmable logic device.

32. (original) The phase-locked loop circuit of claim 1 wherein said oscillator is a voltage-controlled oscillator.

33. (original) The phase-locked loop circuit of claim 1 further comprising an output scaling counter downstream of said output terminal.

34. (original) The phase-locked loop circuit of claim 1 further comprising an input scaling counter upstream of said input terminal.

35. (original) The phase-locked loop circuit of claim 1 further comprising a feedback scaling counter between said output terminal and said feedback path.

36. (original) A programmable logic device comprising the phase-locked loop circuit of claim 1.

37. (original) A digital processing system comprising:

processing circuitry;

a memory coupled to said processing circuitry;

5 and

a programmable logic device as defined in claim 36 coupled to the processing circuitry and the memory.

38. (original) A printed circuit board on which is mounted a programmable logic device as defined in claim 36.

39. (original) The printed circuit board defined in claim 38 further comprising:

memory circuitry mounted on the printed circuit board and coupled to the programmable logic device.

40. (original) The printed circuit board defined in claim 39 further comprising:

processing circuitry mounted on the printed circuit board and coupled to the memory circuitry.

41. (original) An integrated circuit device comprising the phase-locked loop circuit of claim 1.

42. (original) A digital processing system comprising:

processing circuitry;

a memory coupled to said processing circuitry;

5 and

an integrated circuit device as defined in claim 41 coupled to the processing circuitry and the memory.

43. (original) A printed circuit board on which is mounted an integrated circuit device as defined in claim 41.

44. (original) The printed circuit board defined in claim 43 further comprising:

memory circuitry mounted on the printed circuit board and coupled to the integrated circuit device.

45. (original) The printed circuit board defined in claim 44 further comprising:

processing circuitry mounted on the printed circuit board and coupled to the memory circuitry.

46. (currently amended) A programmable logic device comprising:

at least one programmable logic region; and  
a phase-locked loop circuit having an input  
5 terminal for receiving an input signal having a reference frequency and an output terminal for outputting an output frequency phase-locked to said reference frequency, and comprising:

an oscillator for producing said output  
10 frequency, and

a feedback path feeding said oscillator, said feedback path accepting as inputs said reference frequency and said output frequency, and causing said oscillator to drive said output frequency to a phase-frequency lock with said  
15 reference frequency, said feedback path comprising at least one component connected therein, wherein:

one or more of said at least one component is programmably connectable to said programmable logic region for operation of said programmable logic region with said ~~at least~~  
20 one or more of said at least one component.



47. (previously presented) The programmable logic device of claim 46 wherein, when said phase-locked loop circuit is not in use in said programmable logic device, said one or more of said at least one component is available for use by  
5 said at least one programmable logic region.

48. (previously presented) The programmable logic device of claim 46 wherein, when said phase-locked loop circuit is in use in said programmable logic device, at least a portion of said at least one programmable logic region is available to  
5 be substituted in said phase-locked loop circuit for said one or more of said at least one component.

49. (previously presented) The programmable logic device of claim 46 wherein said at least one component comprises:

a phase-frequency detector having as inputs said  
5 reference frequency and said output frequency, said phase-frequency detector outputting a comparison signal indicating a relationship between said reference frequency and said output frequency;

an analog front end circuit having said  
10 comparison signal as an input and outputting an analog voltage signal indicative of said comparison;

an analog-to-digital converter having said analog voltage signal as an input and outputting a digitized voltage signal;

15 a digital signal processor having said digitized voltage signal as an input and outputting a digital control signal; and

a digital-to-analog converter having said digital control signal as an input and outputting an analog  
20 control signal that is input to said oscillator.

50. (previously presented) The programmable logic device of claim 49 wherein said analog-to-digital converter has at least one of:

a second input programmably connectable to a  
5 first said another portion of said programmable logic device;  
and

a second output programmably connectable to a second said another portion of said programmable logic device.

51. (original) The programmable logic device of claim 50 wherein said first said another portion is a pin of said programmable logic device.

52. (original) The programmable logic device of claim 50 wherein said first said another portion is in core logic of said programmable logic device.

53. (original) The programmable logic device of claim 50 wherein said second said another portion is a pin of said programmable logic device.

54. (original) The programmable logic device of claim 50 wherein said second said another portion is in core logic of said programmable logic device.

55. (previously presented) The programmable logic device of claim 49 wherein said digital signal processor has at least one of:

a second input programmably connectable to a  
5 first said another portion of said programmable logic device;  
and

a second output programmably connectable to a second said another portion of said programmable logic device.

56. (original) The programmable logic device of claim 55 wherein said first said another portion is a pin of said programmable logic device.

57. (original) The programmable logic device of claim 55 wherein said first said another portion is in core logic of said programmable logic device.

58. (original) The programmable logic device of claim 55 wherein said second said another portion is a pin of said programmable logic device.

59. (original) The programmable logic device of claim 55 wherein said second said another portion is in core logic of said programmable logic device.

60. (previously presented) The programmable logic device of claim 49 wherein said digital-to-analog converter has at least one of:

5 a second input programmably connectable to a first said another portion of said programmable logic device; and

a second output programmably connectable to a second said another portion of said programmable logic device.

61. (original) The programmable logic device of claim 60 wherein said first said another portion is a pin of said programmable logic device.

62. (original) The programmable logic device of claim 60 wherein said first said another portion is in core logic of said programmable logic device.

63. (original) The programmable logic device of claim 60 wherein said second said another portion is a pin of said programmable logic device.

64. (original) The programmable logic device of claim 60 wherein said second said another portion is in core logic of said programmable logic device.

65. (original) The programmable logic device of claim 49 wherein said analog front end circuit comprises a charge pump.

66. (previously presented) The programmable logic device of claim 46 wherein said at least one component comprises:

5 a phase-frequency detector having as inputs said reference frequency and said output frequency, said phase-frequency detector outputting digital comparison signals indicating a relationship between said reference frequency and said output frequency;

10 a digital counter circuit having said digital comparison signals as inputs and outputting digital count signals indicative of said comparison;

a digital signal processor having said digital count signals as inputs and outputting a digital control signal; and

15 a digital-to-analog converter having said digital control signal as an input and outputting an analog control signal that is input to said oscillator.

67. (previously presented) The programmable logic device of claim 66 wherein said digital signal processor has at least one of:

5 an additional input programmably connectable to a first said another portion of said programmable logic device; and

a second output programmably connectable to a second said another portion of said programmable logic device.

68. (original) The programmable logic device of claim 67 wherein said first said another portion is a pin of said programmable logic device.

69. (original) The programmable logic device of claim 67 wherein said first said another portion is in core logic of said programmable logic device.

70. (original) The programmable logic device of claim 67 wherein said second said another portion is a pin of said programmable logic device.

71. (original) The programmable logic device of claim 67 wherein said second said another portion is in core logic of said programmable logic device.

72. (previously presented) The programmable logic device of claim 66 wherein said digital-to-analog converter has at least one of:

a second input programmably connectable to a  
5 first said another portion of said programmable logic device;  
and

a second output programmably connectable to a  
second said another portion of said programmable logic device.

73. (original) The programmable logic device of claim 72 wherein said first said another portion is a pin of said programmable logic device.

74. (original) The programmable logic device of claim 72 wherein said first said another portion is in core logic of said programmable logic device.

75. (original) The programmable logic device of claim 72 wherein said second said another portion is a pin of said programmable logic device.

76. (original) The programmable logic device of claim 72 wherein said second said another portion is in core logic of said programmable logic device.

77. (original) The programmable logic device of claim 46 wherein said oscillator is a voltage-controlled oscillator.

78. (original) The programmable logic device of claim 46 further comprising an output scaling counter downstream of said output terminal.

79. (original) The programmable logic device of claim 46 further comprising an input scaling counter upstream of said input terminal.

80. (original) The programmable logic device of claim 46 further comprising a feedback scaling counter between said output terminal and said feedback path.

81. (original) A digital processing system comprising:

processing circuitry;

a memory coupled to said processing circuitry;

5 and

a programmable logic device as defined in claim 46 coupled to the processing circuitry and the memory.

82. (original) A printed circuit board on which is mounted a programmable logic device as defined in claim 46.

83. (original) The printed circuit board defined in claim 82 further comprising:

memory circuitry mounted on the printed circuit board and coupled to the programmable logic device.

84. (original) The printed circuit board defined in claim 83 further comprising:

processing circuitry mounted on the printed circuit board and coupled to the memory circuitry.